

2016 CITIZEN 1



Azurite Blue



Black Coal

SPECIFICATIONS

Frame	Hi-Tensile steel frame, sloping design for men's, step through design for ladies, center-mount kickstand plate and fender/rack mount eyelets
Fork	Hi-tensile steel unicrown, radius blades with dropout eyelets
Headset	Water-resistant sealed mechanism, threaded, 1 1/8"
Wheels	Alex alloy rims, 36H, Formula alloy hubs with QR and 14g stainless steel spokes
Tires	CST Marathon/Tour with silver safety stripe, 700 x 38c
Derailleurs	Shimano Tourney, TX55 rear and Shimano TX51 front, 31.8mm clamp, top swing/dual pull front.
Shiftlevers	Shimano Revoshift, SL-RS35, 21-speed
Chain	KMC UG51
Cassette	Shimano MF-TZ31 7-Speed 14-34T
Crankset	Shimano FC-M131 triple, 48/38/28T, 170mm with chainguard
BB Set	VP sealed cartridge, 68 x 122.5mm
Pedals	Comfort platform style
Brakeset	Forged alloy linear-pull brakes with Tektro CL530 ergonomic designed alloy brake levers with kraton insert
Handlebar	Comfort hi-rise, steel, 25.4 x 80mm rise x 15° sweep x 640mm
Stem	Jamis alloy hi-rise, 35° rise x 90mm with 150mm quill (14-18"), 110mm with 180mm quill (19-23")
Grips	New anatomic triple density kraton grip with reflective end plug
Seat Post	Jamis alloy micro-adjust, 25.4 x 350mm with alloy QR clamp. 300mm for Men's 15, 17, Step-Thru 14
Saddle	Jamis Comfort with synthetic suede cover, burnished sides and bumper springs with satin steel rails, gender specific
Accessories	Kickstand
Sizes	M: 15", 17", 19", 21", 23" S/T: 14", 18"
Color	M: Black Coal or Azurite Blue S/T: Cucumber or Violet

UPGRADES/CHANGES FROM 2015

Same great spec and quality

TOP 5 THINGS YOU NEED TO KNOW

A Shimano group ensures the quickest, most reliable shifts every time, all the time. The 21-speed Revo twist-shifting drivetrain with Shimano M131 48/38/28 crankset, TX55 rear & TX51 front derailleurs and 14-34 Mega-Range freewheel offers a much larger gear range, with much lower gearing, for easier hill climbing than standard or compact double chainring road and street bikes.

CST's Marathon/Tour tire features a smart tread design for secure grip and low rolling resistance on roads & pathways. And their generous 700 x 38c casing size holds more air volume & is more comfortable to ride than narrower 23 - 28C road tires.

A near all-alloy parts list -- alloy micro-adjust seat post, alloy stem, alloy crank, alloy hubs, alloy rims, alloy brakes & levers -- reduces weight, adds value and is rust-proof.

We offer super plush comfort saddles with slip resistant suede-type top, "thigh glide" burnished sides, elastomer springs -- with male & female specific saddle lengths & widths.

Tektro's brake levers offer slip-resistant, shock-absorbing inserts on the finger contact points for more secure, comfortable braking

GEOMETRY

SIZE	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
15	21.50 / 546	70°	74°	17.52 / 445	41.61 / 1057	1.97 / 50	11.22 / 285	4.72 / 120	28.35 / 720
17	22.11 / 562	70°	74°	17.52 / 445	42.24 / 1073	1.97 / 50	11.22 / 285	4.72 / 120	28.82 / 732
19	22.48 / 571	71°	73.5°	17.52 / 445	42.01 / 1067	1.97 / 50	11.22 / 285	4.72 / 120	30.04 / 763
21	23.06 / 586	71°	73.5°	17.52 / 445	42.64 / 1083	1.97 / 50	11.22 / 285	5.12 / 130	31.49 / 800
23	23.46 / 596	71°	73.5°	17.52 / 445	43.03 / 1093	1.97 / 50	11.22 / 285	5.71 / 145	32.40 / 823
14 S/O	21.49 / 546	70°	74°	17.52 / 445	41.69 / 1059	1.97 / 50	11.22 / 285	5.90 / 150	19.05 / 484
18 S/O	21.88 / 556	70°	73.5°	17.52 / 445	41.93 / 1065	1.97 / 50	11.22 / 285	6.49 / 165	18.54 / 471