2016 TRAIL XR

Ano Black

SPECIFICATIONS

Frame	Hi-tensile steel tubes
Fork	Unicrown, hi-tensile steel, with over-sized radiused blades
Headset	VP threaded
Wheels	Alloy 26 x 1.50" 36H rims, heavy-duty ATB hubs with QR, stainless spokes
Tires	Kenda 50-Fifty, 26 x 1.95"
Derailleurs	SRAM X3 rear and Shimano TZ30 front
Shiftlevers	SRAM 3.0 Grip Shift, 3x7-speed
Chain	KMC Z51, 7-speed
Cassette	7-speed freewheel, 13-28T
Crankset	Forged alloy crank, 42/34/24T, 170mm
BB Set	VP bolt type axle
Pedals	ATB platform, hi-impact resin
Brakeset	Alloy linear pull type with full alloy 4-finger levers
Handlebar	Jamis XC riser, 25.4 x 20mm rise x 620mm
Stem	Jamis Hi-Rise, 40˚ rise x 90mm (12-14"), 100mm (15-18"), 120mm (19-21")
Grips	Kraton for Grip Shift
Seat Post	Jamis alloy micro-adjust, 28.6 x 350mm (12-15") 400mm (17-21")
Saddle	Jamis ATB Sport, SL cover, protective front and rear guards
Sizes	M: 13", 15", 17", 19", 21" S/O: 12", 14", 18"
Color	M: Electric Blue or Ano Black S/O: Ultraviolet or Seafoam

UPGRADES/CHANGES FROM 2015

Kenda 50-Fifty tires

TOP 5 THINGS YOU NEED TO KNOW

Our straight-bladed tubular unicrown fork is significantly lighter than most suspension forks, offering more responsive steering and an easier to lift-up-the-dorm-stairs bike.

XR's 21-speed SRAM twist-shift drivetrain shifts intuitively and smoothly. With 3 chainrings up front and a 13-28T indexed freewheel in back, steep hills are flattened and fun.

Every Trail XR offers quick release front & rear wheels and a quick release saddle assembly to make transport, storage, or locking up a snap.

That long-quilled, hi-rise stem positions the XR riser handlebar higher than on our other Trail series bikes with threadless steering systems for a more propped-up, less-weight-on-the-wrists riding position.

There's lots of lightweight, rust-proof alloy parts on the XR -- micro-adjust seat post, crank, seat post clamp, rims and brakes -- that make riding more pleasurable & maintenance easier.

RECREATION - Comfort

GEOMETRY

SIZE	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER
13	20.86 / 530	70.5˚	74˚	16.73 / 425	40.35 / 1025	1.77 / 45	1.3 / 33	4.13 / 105	26.22 / 666
15	21.42 / 544	70.5˚	74˚	16.73 / 425	40.90 / 1039	1.77 / 45	1.3 / 33	4.72 / 120	28.07 / 713
17	21.89 / 556	71˚	73.5˚	16.73 / 425	40.98 / 1041	1.77 / 45	1.3 / 33	4.92 / 125	29.01 / 737
19	22.52 / 572	71˚	73.5˚	16.73 / 425	41.65 / 1058	1.77 / 45	1.3 / 33	5.12 / 130	30.27 / 769
21	23.34 / 593	71.5˚	73˚	16.73 / 425	42.12 / 1070	1.77 / 45	1.3 / 33	6.49 / 165	31.96 / 812
12	20.51 / 521	70.5˚	74˚	16.93 / 430	40.16 / 1020	1.77 / 45	1.3 / 33	4.13 / 105	24.52 / 623
14	20.71 / 526	70˚	73˚	16.93 / 430	40.23 / 1022	1.77 / 45	1.3 / 33	4.92 / 125	25.27 / 642
18	21.97 / 558	70.5˚	72.5˚	16.93 / 430	41.10 / 1044	1.77 / 45	1.3 / 33	5.51 / 140	25.59 / 650